

KPREMIUM1KC

Part number: F101000C

UPS On-Line double conversion 1000VA



APPLICATION FIELDS

Input voltage (Vac)	230 Vac
Output voltage	230 Vac
Phase	Single
Rack units	-
Output frequency (Hz)	50 - 60
Harmonic distortion (%THD)	<3
Power (kVA)	1
POWER (VA)	1000
Power (W)	900
Technology	On-line
Installation	Tower
Input frequency (Hz)	50 - 60
Input power factor	0,99
Wave form	Pure sine wave
Output power factor	0,9
Signalling	Low battery voltage, Overload, Operated batteries , Battery fault
Expandable backup time	yes

Connection	Plug-in
IP rating	IP20
BACKUP TIME (min)	10
Overload	1s - 120%
By-pass	yes
Transfer time (ms)	0
Crest factor	3 ÷ 1
Standard provided equipment	Output cable, Input cable
Protections	Excessive battery discharge, Overload, Short circuit, Thermal, Overvoltage
Audible noise at 1m (dBA)	<55
Working temperature (°C)	0 +40
Parallel connection	No
Communication	USB
Information on the display	Alerts / Error, Low battery voltage, Connected load, Battery Mode, Load level, Input Voltage, Output Voltage
EPO - Emergency power off	yes
Recharge time	7h to 90% of full capacity
Battery type	Sealed lead acid, maintenance-free
Standards	EN 61000-4-2, EN 61000-4-4, EN 62040-1, Directive (LVD) 2014/35/UE, Directive (EMC) 2014/30/UE, EN 61000-4-3, EN 61000-4-5
Warranty	2 Year
Height (mm)	230
Width (mm)	144
Depth (mm)	350
Weight (Kg)	10