

## SEI-E8120TI



**Eyeball IP, 4K(8MP), 2.8mm, ICR, dWDR, LEDs 20-30mt, IP67/IK10, POE, VCA Basic, H.265, MIC**

- 4K Resolution for super detailed images
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- ONVIF protocol support
- Power-over-Ethernet support
- IP67 Ingress protection

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Image Sensor</b>	1/2.7" progressive scan CMOS
<b>Pixels - Total</b>	3840 (H)x 2160 (V)
<b>Video Resolution</b>	1280x720 (720p), 1920x1080 (1080p), 720x576 (D1), 3840 x 2160 (25fps)
<b>Scanning System</b>	Progressive
<b>Col/B</b>	On/Off/Auto
<b>Sensitivity B/W</b>	0 Lux LED IR on, 0.032 lux @ F1.2
<b>Lens Focal Length</b>	2.8 mm
<b>Horizontal Viewing Angle</b>	112°
<b>Video Outputs</b>	1x CVBS (1Vpp), BNC
<b>Shutter Speed</b>	1/25 ~ 1/100,000s
<b>Max. IR Distance</b>	20/30m (according to scene reflexion)
<b>WDR</b>	D-WDR (Digital wide dynamic range)
<b>Intelligent Video Analytics</b>	Tampering, Motion /Moved-Fixed Objects /Fence /Enter-Exit Area
<b>White Balance</b>	Auto / Manual
<b>AGC</b>	Auto, Manual
<b>Digital Noise Reduction</b>	Auto (3D-DNR)
<b>De-Fog</b>	Off/On
<b>Video Compression</b>	H.264, H.265, Triple Streaming
<b>ONVIF compliant</b>	Profile S
<b>Max. Users</b>	3
<b>SD memory</b>	Micro SD/SDHC
<b>Alarm</b>	N/A
<b>Audio Inputs</b>	1 in Mic, Built in Microphone
<b>Audio Outputs</b>	1 CH, Line out, None
<b>Audio Compression</b>	G.711 a/u
<b>Web Browser</b>	All major browsers are supported
<b>Network Protocol</b>	HTTPS, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Interfaces</b>	RS-485
<b>Supply Voltage</b>	12 Vdc / PoE (IEEE 802.3af)
<b>Protection Rating</b>	IK10, IP67
<b>Firmware Upgrade</b>	Firmware upgrade by Web Browser

## SEI-E8120TI

**Technical Specifications**

Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Power Consumption (W)	6
Weight	0.47 kg - 1.04 lbs
Dimensions	Ø 94.6 mm - 3.72 In