# SEI-X6121TI







### Fisheye IP, 6MP, ICR, dWDR, IR 15m, IP66, PoE, H.265

- 6 Megapixels Fisheye Camera
- Triple-streaming support
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- IP 66 Certification
- Built-in IR LED Illuminator

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, form retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.



TKH SECURITY SOLUTIONS AASSET SECURITY - Via Palù 38 h/I - 31010 Zoppé di S. Vendemiano (TV) - Italia Tel : +39 0438 1792811 - Fax : +39 0438 1792831

# SEI-X6121TI

#### **Technical Specifications**

| Image Sensor             | 1/2.9" Progressive Scan CMOS [COPY]                 |
|--------------------------|---|
| Pixels - Total           | 2160(H)x2160(V)                                     |
| Scanning System          | Progressive   |
| Col/B                    | On/Off/Auto   |
| Lens Focal Length        | 1.07mm  |
| Iris F-Number            | F2.5  |
| Shutter Speed            | 1/25 ~ 1/100,000s                                   |
| Max. IR Distance         | 15m   |
| WDR                      | D-WDR (Digital wide dynamic range)                  |
| White Balance            | Auto / Manual                                       |
| AGC                      | Auto, Manual  |
| Digital Noise Reduction  | Auto (3D-DNR)                                       |
| Video Compression        | H.264, MJPEG, H.265, Triple Streaming               |
| Video Resolution         | 30fps@(2160x2160/1920x120/1440/1440)                |
| ONVIF compliant          | Profile S   |
| Max. Users               | 10  |
| Web Browser              | All major browsers are supported                    |
| Network Protocol         | TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP |
| Network Interface        | 1x 10/100 Base T/TX (RJ-45)                         |
| Protection Rating        | IP66  |
| Firmware Upgrade         | Firmware upgrade by Web Browser                     |
| Operating Temperature    | -20°C ~ +50°C                                       |
| Humidity                 | 10 ~ 90%RH  |
| Supply Voltage           | 12 Vdc, PoE (IEEE 802.3af)                          |
| Horizontal Viewing Angle | 180 (wall mount) 360 (ceiling mount)                |
| Power Consumption (W)    | 12  |
| Weight                   | 0.432 kg - 0.95 lbs                                 |
| Dimensions               | ø 130 mm - 5.12 ln                                  |

skill**eye** 

Т<Н



ASSET

JRITY JTIONS AASSET SECURITY - Via Palù 38 h/I - 31010 Zoppé di S. Vendemiano (TV) - Italia Tel : +39 0438 1792811 - Fax : +39 0438 1792831