

ATS8520-2

User management tool, USB version

Product overview

ATS8520 provides an easy, open look Windows® interface that simplifies the user management or control of Advisor Advanced or Advisor MASTER panels. Up to 20 panels can be managed separately. Each panel is configured one by one.

Upload / download

A PC running ATS8520 can be connected to a control panel either remotely via the built-in PSTN dialer or ethernet/GPRS connection. Changes made to user configuration can be up/downloaded (all data) or synchronized (changes only).

Remote Command and Control

All Advisor Advanced control panels can run a Command & Control session with the ATS8520. It will provide a complete overview of the panel status including zone, area, communication path, etc. The ATS8520 can provide full control over the panel remotely based on the user options assigned.

Real time event log

A real-time event log shows all events as they happen with a time and date stamped description of the event. History can be viewed as a constantly visible window in the Command & Control view.

Supported languages

The ATS8520 supports following languages:
Danish, Norwegian, Finnish, Swedish, French, Turkish, Polish, Slovak, Czech, Dutch, English Irish, English UK, French, German, Italian, Portugal and Spanish.

User management

User management includes operations related to create, modify or remove users, PIN codes of users, card assignment, access right assignment or schedules and holidays.



Dettagli

- User management tool for smaller systems, managing up to 20 panels separately
- Configure and modify users, assign cards and PIN codes
- Microsoft SQL database
- Command & Control with live history
- Real time event logging
- Manage schedules and holidays

ATS8520-2

User management tool, USB version

Specifiche tecniche

Generale

Linee prodotto	Advisor Advanced, ATS Master
Segmentazione	Commerciale
Tipo Software	Software gestionale
Tecnologia supportata	Access Control, Intrusione
Hardware supportato	Advisor Advanced, ATS Master

Dettagli software

Architettura software	Standalone
Tipo licenza	Licenza gratuita

Requisiti di sistema

Sistema operativo supportato	Windows 10, Windows 7, Windows 8.x
Supporto database	SQL
Requisiti minimi di sistema	Intel Dual Core i5 with 4GB RAM Memory: 256 MB (minimum); 1GB (recommended) HDD: Up to 500 MB of available space may be required Display: 1024 x 768, 32-bit (minimum), Note: for Windows 7, Home and Starter Editions are not supported.

Fisico

Peso netto	80 g
Peso spedizione	110 g

General

Max. number of PC with ATS8520 connected	1
Max. number of panels connected at the same time	20
Number of panels in database	20



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 10:33