



Pan-Net® Copper Patch Cord

UTP28SP2MBU

The TX6-28™ Cat 6 UTP Patch Cord is a 2-Meter, 0.150-inch (3.8mm) diameter, Blue cord constructed of 28 AWG, unshielded, twisted pair, stranded, CM/LSZH cable with high-performance modular plugs. Its compact 28 AWG design simplifies installation and management. The tangle-free latch prevents snags and ensures a fast release, streamlining moves, adds, and changes. Enabled with RapidID, the product has pre-installed barcodes for simple port mapping using RapidID software.

Specifications

Application	(1) 1000BASE-T (Gigabit Ethernet), 100BASE-T (Fast Ethernet) (2) 155 Mb/s ATM, 622 Mb/s ATM, 1.2 Gb/s ATM (3) Digital video and broadband/baseband analog video(4) Voice/data systems (5) Voice over Internet Protocol (VoIP)
Product Type	Copper Patch Cord
Conductor Gauge (AWG)	28
Sub Brand	Pan-Net®
Performance Level	Category 6
Conductor Type	Stranded
Cable Construction	U/UTP
Jacket Material	LSZH Material
Connector 1 Type	RJ45 8
Connector 2 Type	RJ45 8
Overall Length (m)	2
Nominal Cable Outside Diameter (mm)	3.8
Maximum Operating Temperature (°C)	75
Minimum Operating Temperature (°C)	-10
Boot Color	Clear
Color	Blue
Flammability Rating	Dual Rated (CM/LSZH)
RapidID™ Enabled	Yes

Packaging Detail

UPC	07498365691
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0177
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.1773