

SEN-K8801S1-2LAN


NVR 8 In, H.265, max 8MP, 80Mbps, no POE, HDMI 4K, Fisheye, Face Recognition, Fanless, 2 Lan.

- Operating System - Linux Embedded
- H.264/H.265 compression modes
- Up to 8 cameras with 8MP
- Pentaplex: preview, record, playback, backup and remote access
- Smart Phone support Android, iPhone and iPad
- 4K video display on main HDMI
- Free DDNS service
- Fish eye 360° camera dewarp function for live and playback (using compatible VMS)

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEN-K8801S1-2LAN

Technical Specifications

Operating System	Embedded Linux
Multiplex Function	Pentaplex
Basic Internal Storage	0 GB
Max. Storage Capacity	1 Hard disk (3.5 inch SATA), up to 8TB
Video Inputs	8 IP cameras
Recording Bandwidth	max. 80 Mbps
HDMI/VGA output	Up to 8 Megapixel
Video Compression	H.264, H.265
Video Streaming	2 independent Video-Streams
Video Outputs	1x HDMI, 1x VGA
Display resolution	Up to 4K on HDMI, VGA: 1920x1080, 1280x1024
Display Speed	200 fps
Audio Inputs	1 CH, RCA, 8 CH over IP
Audio Outputs	1 CH, RCA
Recording Mode	Manual, Schedule, Motion, Alarm, VCA from IP camera
Alarm Inputs	8, Support IPC alarm input
Alarm Outputs	4, Support IPC alarm output
Motion Detection	On/ Off/ Area Setting
Intelligent Video Analytics	Motion /Moved-Fixed Objects /Fence /Enter-Exit Area
Alarm Trigger	Alarm Input, Manual Trigger, Motion detection, System Exceptions, Video Loss
Face recognition	Professional Face Detection, Face Recognition
Fisheye settings	360°, Panoramic View, 2x180°, 4 Windows
Alarm Notification	Email / FTP, Pop-up video, Preset on PTZ, Relay, Snapshot Record, Video Record
Interfaces	RS-485, 1 x USB 2.0, 1 x USB 3.0
Network Interface	2x 10/100/1000 Base T/TX (RJ-45)
Max power Output per Port	DC 48V, 15.4W
Network Protocol	AutoDDNS, AutoNAT, DDNS, DHCP, DNS, NTP, PPPoE, QRCode, SMTP, TCP/IP, UPnP
Monitoring	Web viewer, CMS (Microsoft Windows & Apple macOS), Smartphone viewer (iOS, Android)
Max. Users	10
Playback	Synchronised playback of max. 8 cameras
Search Mode	Time, Motion, Alarm, Timeline

SEN-K8801S1-2LAN**Technical Specifications**

Smart Search Function	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
External Backup	USB HDD, USB Memory, Network
Supply Voltage	12 Vdc, Power adaptor included
ONVIF compliant	Yes
Operating Temperature	-10°C ~ +50°C
Operating Humidity	10% ~ 90%, non-condensing
Dimensions (W x H x D)	300 x 45 x 249 mm - 11.81 x 1.77 x 9.8 In
Power Consumption (W)	10
Weight	2.3 kg - 5.07 lbs