

ATS1100

Tastiera con display LCD. IMQ II liv.

Remote Arming Stations

The ATS 1100 is part of the Remote Arming Station family for the advisor MASTER security system. The RAS family consists of a range of keypads and card readers which can be used in different environments, in and out-door. The ATS1100 can be used for configuration and management of the system, as well as for opening doors and arming/disarming areas. In an easy way, the ATS1100 gives a status overview from your security system with both visual and audio indicators.

Product Overview

The ATS1100 has a clearly readable text on a 2 x 16 characters LCD for displaying system programming, alarm and access control functions. It can be mounted at a distance of 1.5 km from an advisor MASTER panel. The Arming Station can display the status of 8 area's using LED's, while the LCD shows details of alarms or a pre-programmed text.

Installation

The ATS 1100 has 4 free programmable function buttons to active the macros. To navigate through the programming and operational features, even in places where lightning is poor, the backlit screen and keys highlight the keypad for day and night use. The backlit functionality is freely programmable.

Indications

In non-alarm situation the keypad can scroll a free programmable text. Area numbers, displayed on the front of the Arming Station, have corresponding status indicator LED's. An LED flashes when an area is in alarm, is off when an area is disarmed and is constantly lit when an area is armed. Dipswitches on the Arming Station determine whether the area LED's represent the first 8 areas in a total of 16 or the second 8, depending on client requirements and the location of the Arming Station.



Dettagli

- Certificazione IMQ Allarme II° Livello
- Display retroilluminato con 2 righe da 16 caratteri ciascuna
- 3 LED per indicazione dello stato del sistema
- 8 LED per indicazione dello stato delle aree
- 4 pulsanti funzione liberamente programmabili
- Layout dei tasti standard
- Linea moderna ergonomica

ATS1100

Tastiera con display LCD. IMQ II liv.

Specifiche tecniche

Generale

Interfaccia utente	2 x 16 Char LCD, Touch Buttons
Linee prodotto	ATS Master
Lettori integrati	Prossimità

Sistema

Tipo di indirizzamento	DIP Switches
Tipo di cavo supportato	Aritech WCAT 52/54 or equivalent

Comunicazione

Tipo di comunicazione	Cablato
-----------------------	---------

Ingressi / Uscite

Ingressi	1
Tipo di input	Request to Exit
Uscite	1
Tipo di uscita	50 mA Max

Elettrico

Tensione di esercizio	10.5 to 13.8 VDC
Power supply type	VDC
Consumo attuale	185 mA max

Fisico

Dimensioni fisiche	126 x 168 x 40 mm (W x H x D)
Colore	Beige
Fattore di forma	Verticale
Cover	Flip Cover
Tipo di montaggio	Montaggio a superficie

Ambientale

Temperatura operativa	0 to +50°C
IP rating	IP30



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:32