

SEI-T8123TI-28



Bullet IP, 8Mpxl, 2.8mm, ICR, WDR 120dB, LEDs 30-50mt, IP67/IK10, POE, H.265, Face Detection, ADVANCED VCA A

- 4K Resolution for super detailed images
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Advanced Analytics with car\human\bike classification
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- ONVIF protocol support
- Power-over-Ethernet support
- IP67 Ingress protection

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/2.8" Progressive Scan CMOS
Pixels - Total	3840 (H)x 2160 (V), 25fps
Video Resolution	1080p (1920x1080); 720p(1280x720); 1024x768; 800x600; D1 (720x576); CIF (352x288) , 3840 x 2160 (25fps), 4MP (2592x1520)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity Colour	0.01 lux @ F1.2
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	2.8 mm
Field of View	H : 109.7° / V : 77.2°
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	70 m
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, H.264+, Triple Streaming
ONVIF compliant	Profile S
Advanced Video Analytics	Advanced video Analytics A: Area intrusion\line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crowd detection, people counting, car counting, heat mapping, human & face tracking.
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
VCA Distance	Human: 8 m, Vehicle: 15 m
Max. Users	10
SD memory	supports up to 128 GB capacity of micro TF Card
Alarm	N/A
Audio Inputs	1 CH, Line in
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)

Technical Specifications

Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Dimensions (W x H x D)	80.5 x 80.5 x 217.7 mm - 3.17 x 3.17 x 8.57 In
Power Consumption (W)	9
Weight	0.648 kg - 1.43 lbs