

SEI-Q4120TIA


Cube Camera, 2MP, 2.8mm, ICR, dWDR, LEDs 10mt, Audio MIC & Speaker, WiFi, PIR Alarm, POE, H.265

- 2 Megapixel IP Camera with Full HD 1080P real time video
- Support Wifi
- Triple-streaming support
- H265 for high compression rate and stable stream control
- ONVIF protocol support
- Power-over-Ethernet support
- Day/Night feature with IR cut filter removable, for higher sensitivity and vibrant colors
- Built-in IR LED Illuminator

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/2.7" progressive scan CMOS
Pixels - Total	1920(H) x 1080(V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.007 lux @ F1.2
Lens Focal Length	2.8 mm
Horizontal Viewing Angle	116.6°
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	10 m
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, Triple Streaming
Video Resolution	1920x1080 (1080p), 1280x720 (720p), 3MP 2304 (H) x1296 (V), 5M 2592x1944 (20fps), 4M 2592x1520 (30fps)
ONVIF compliant	Profile S
Max. Users	4
Audio Compression	G.711A
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	Indoor Applications only
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-10°C ~ +45°C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Dimensions (W x H x D)	130 x 71.7 x 71.7 mm - 5.12 x 2.82 x 2.82 In
Power Consumption (W)	4.5
Weight	0.14 kg - 0.31 lbs