

AS508

Outdoor siren with single amber beacon and inner metal shield



Details

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- Metal Inner cover
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Fully compliant with CE, BS and IS requirements
- Self detection of cable cutting or tampering
- Installer Friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

AS508

Outdoor siren with single amber beacon and inner metal shield

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	114 dB at 1 m (typical)

Flash specifications

Flash frequency	50 to 60 flashes/min
-----------------	----------------------

Electrical

Operating voltage	10 to 14.5 VDC
Current consumption	350 mA 40 mA (standby, with NiCd battery) 20 mA (standby, without battery)

Physical

Physical dimensions	210 x 300 x 55 mm
Net weight	1235 g
Material	ABS

Environmental

Operating temperature	-25 to 55°C
IP rating	IP54

Material

	ABS (3 mm)
--	------------

Sounder

	Double piezo
--	--------------

PCB protection

	Fully potted
--	--------------

Tamper & pry-off

	Yes
--	-----

Frequency

	0.5 to 3 kHz
--	--------------

Cut-off timer

	3, 5, 10, 20 min
--	------------------

Comfort LED

	Yes
--	-----

Low voltage detection

	Yes
--	-----

Metal inner cover

	Included
--	----------

Optional self-activating battery

	10.8 V / 280 mAh
--	------------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 29 August 2023 - 9:44