

AI671

Indicatore remoto minidisc

General

The AI671 remote indicator is a lightweight, compact indicator for use in fire protection systems. It may be used in all installations incorporating 600, 800 and 900 series detectors, including the 630, 650, 860, 930, 950 and 990 series, as well as in intrinsically safe applications using the 670 and 970 series detectors.

Features

The AI671 is only 20 mm high and 80 mm in diameter. It comprises two parts - the base that is installed onto a wall or ceiling, and the lid that is fitted to the base with a bayonet lock. An anti-tamper screw in the lid locks the unit together.

Two pairs of keyholes are provided - one for 50 mm and the other for 60 mm fixing centres.

Installation

The AI671 is polarity sensitive.



Dettagli

- Small and non-intrusive
- Low profile
- Anti-tamper fitting
- Mounting holes for 50 or 60 mm fitting

AI671

Indicatore remoto minidisc

Specifiche tecniche

Elettrico

Operating voltage	5 to 36 VDC
-------------------	-------------

Current consumption	25 mA up to 40°C
---------------------	------------------

Fisico

Physical dimensions	80 x 20 mm (Ø x H)
---------------------	--------------------

Ambientale

Temperatura operativa	-10 to +60°C
-----------------------	--------------

Environment	Interno
-------------	---------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 31 May 2023 - 12:24