

## SEI-F7120TI-28


**Minidome Flat IP, 5MP, 2.8mm, ICR, WDR(120dB), LEDs 10mt, IP66, PoE, VCA Basic, Microfono**

- 5 Megapixel resolution
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- Power-over-Ethernet support
- IP66 Ingress protection

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Image Sensor</b>	1/2,5" Progressive Scan CMOS
<b>Pixels - Total</b>	2592(H) x 1944(V)
<b>Scanning System</b>	Progressive
<b>Col/B</b>	On/Off/Auto
<b>Sensitivity Colour</b>	0,036 lux @ F2
<b>Sensitivity B/W</b>	0 Lux LED IR on
<b>Lens Focal Length</b>	2.8 mm
<b>Iris F-Number</b>	F 2.0
<b>Horizontal Viewing Angle</b>	85°
<b>S/N Ratio</b>	>50 dB
<b>Shutter Speed</b>	1/25 ~ 1/100,000s
<b>Max. IR Distance</b>	10 m
<b>Intelligent Video Analytics</b>	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
<b>WDR</b>	120dB
<b>White Balance</b>	Auto / Manual
<b>AGC</b>	Auto, Manual
<b>Digital Noise Reduction</b>	Auto (3D-DNR)
<b>Video Compression</b>	H.264, H.265, MJPEG, Triple Streaming
<b>Video Resolution</b>	1920x1080 (1080p), 1280x720 (720p), 720x576 (D1), 4MP 2592 (H) x 1520 (V)
<b>ONVIF compliant</b>	Profile S
<b>Max. Users</b>	10
<b>Audio Inputs</b>	1 in Mic
<b>Audio Compression</b>	G.711A
<b>Motion Detection</b>	Yes
<b>Web Browser</b>	All major browsers are supported
<b>Network Protocol</b>	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Protection Rating</b>	IP66, IK10
<b>Firmware Upgrade</b>	Firmware upgrade by Web Browser
<b>Operating Temperature</b>	-30° C ~ +60° C
<b>Humidity</b>	less than 95%, non condensing
<b>Supply Voltage</b>	12 Vdc, PoE (IEEE 802.3af)
<b>Power Consumption (W)</b>	4.5
<b>Weight</b>	0.349 kg - 0.77 lbs
<b>Dimensions</b>	Ø 110 mm - 4.33 In