

## SEI-P4520TIO


**PTZ Dome Camera IP, 2MP, Starlight, 20x Zoom, IR LEDs 150mt, ICR, WDR, IP66, H.265, 12VDC**

- 2 Megapixel PTZ IP Starlight Camera Real Time Streaming [COPY]
- 20x optical zoom
- Integrated IR LEDs 150m range
- 0 Lux: Integrated LED IR Illuminator to see even in total darkness
- High Speed Pan/Tilt (240°/sec Pan 160°/sec Tilt)
- Colour/B&W function with removable IR cut filter
- Operating Temperature (-30°C~ 60°C)
- TVS 6KV lightning protection, surge protection

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

Image Sensor	1/2,8" Starlight Progressive Scan CMOS
Scanning System	Progressive
Video Resolution	2048x1536 (25 fps)
Col/B	On/Off/Auto, IR-cut filter removable (ICR)
Lens Focal Length	5.5 ~ 110 mm
Optical Zoom Ratio	30x
Lens Drive Type	Auto Iris (DC)
Max. IR Distance	150m
Alarm Inputs	None
Alarm Outputs	None
S/N Ratio	>50 dB
White Balance	Auto / Manual
WDR	True WDR
DNR	Yes
Network Protocol	DHCP, TCP/IP, NTP, PPPoE, UDP, RTSP, SMTP, FTP, DDNS
Video Compression	H.264, H.265
Streaming	Triple Streaming
Alarm Notification	Email / FTP, Snapshot Record, Preset on PTZ, Pop-up video, Relay
Network Interface	10/100 Base-T
Web Browser	All major browsers are supported
PTZ Control	3D Intelligent Position
Pan Speed	max. 240°/s
Tilt Speed	max. 160°/s
Range Panning	360° endless
Number of Preset	360
Number of Pattern	8
Home position	Preset/Sequence/Auto Pan/Cruise
Auto Flip	Yes
OSD	Yes
Protection Rating	IP66
Surge protection maximum voltage	Transient voltage 6000V
Operating Temperature	-30°C ~ +60°C

## SEI-P4520TIO

**Technical Specifications**

Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, Power adaptor included
Accessories included	Bracket & PSU included
Power Consumption (W)	20
Weight	2.1 kg - 4.63 lbs
Dimensions	Ø 173 mm - 6.81 In