

## SEI-X6122TI

**Fisheye IP, 6MP, ICR, dWDR, IR 20-30m, IP67, PoE, Microfono, H.265**

- 6 Megapixels Fisheye Camera
- Triple-streaming support
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- Built-in IR LED Illuminator
- IP67 Ingress protection

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## SEI-X6122TI

### Technical Specifications

Image Sensor	1/2.9" Progressive Scan CMOS [COPY]
Pixels - Total	2160(H)x2160(V)
Scanning System	Progressive
Col/B	On/Off/Auto
Lens Focal Length	1,1mm
Iris F-Number	F2.5
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	20/30m (according to scene reflexion)
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265, Triple Streaming
Video Resolution	30fps@(2160x2160/1920x120/1440/1440)
ONVIF compliant	Profile S
Max. Users	10
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTP, SNMP, IPv4/IPv6, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Audio Outputs	1 CH, RCA
Audio Inputs	1 CH, RCA, Built in Microphone
SD memory	up to 256 GB
Protection Rating	IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Horizontal Viewing Angle	180 (wall mount) 360 (ceiling mount)
Alarm Input/Output	1 ch alarm in . 1 ch alarm out
Power Consumption (W)	12
Weight	0.45 kg - 0.99 lbs
Dimensions	Ø 130 mm - 5.12 In