

## SEN-G4322H1


**NVR 4 In, H.265, max 5MP, 32Mbps, no POE, HDMI 2K, VGA, Fanless.**

- Operating System - Linux Embedded
- Support up to 5MP Resolution Recording
- H.264/H.265 compression modes
- Pentaplex: preview, record, playback, backup and remote access
- Smart Phone support Android, iPhone and iPad
- ONVIF protocol support
- Free DDNS service

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## Technical Specifications

<b>Operating System</b>	Embedded Linux
<b>Multiplex Function</b>	Pentaplex
<b>Basic Internal Storage</b>	0 GB
<b>Max. Storage Capacity</b>	1 Hard disk (3.5 inch SATA), up to 6TB per disk
<b>Video Inputs</b>	4 IP cameras
<b>Recording Bandwidth</b>	max. 32 Mbps
<b>HDMI/VGA output</b>	Up to 5 Megapixel
<b>Video Compression</b>	H.264, H.265
<b>Video Streaming</b>	2 independent Video-Streams
<b>Video Outputs</b>	1x VGA, 1x HDMI
<b>Display Speed</b>	100 fps
<b>Audio Outputs</b>	1x HDMI
<b>Recording Mode</b>	Manual, Schedule, Motion, Alarm
<b>Alarm Inputs</b>	None, Support IPC alarm input
<b>Alarm Outputs</b>	None
<b>Motion Detection</b>	On/ Off/ Area Setting
<b>Alarm Trigger</b>	Alarm Input, Manual Trigger, Motion detection, System Exceptions, Video Loss
<b>Alarm Notification</b>	Email / FTP, Pop-up video, Preset on PTZ, Snapshot Record, Video Record
<b>Interfaces</b>	2 x USB 2.0
<b>Network Interface</b>	10/100 Base-T
<b>Network Protocol</b>	AutoDDNS, AutoNAT, DDNS, DHCP, DNS, NTP, PPPoE, QRCode, SMTP, TCP/IP, UPnP
<b>Monitoring</b>	Web viewer, CMS (Microsoft Windows & Apple macOS), Smartphone viewer (iOS, Android)
<b>Max. Users</b>	10
<b>Playback</b>	Synchronised playback of max. 4 cameras
<b>Search Mode</b>	Time, Motion, Alarm, Timeline
<b>Smart Search Function</b>	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
<b>External Backup</b>	USB HDD, USB Memory, Network
<b>Supply Voltage</b>	12VDC, Power adaptor included
<b>ONVIF compliant</b>	Yes
<b>Operating Temperature</b>	-10°C ~ +50°C

**SEN-G4322H1****Technical Specifications**

<b>Fan</b>	Fanless
<b>Operating Humidity</b>	10% ~ 90%, non-condensing
<b>Dimensions ( W x H x D)</b>	255 x 42 x 233 mm - 10.04 x 1.65 x 9.17 In
<b>Power Consumption (W)</b>	6
<b>Weight</b>	2.3 kg - 5.07 lbs