



Minidome IP AV, 5Mpxl, 3.3-12mm MOTOR., H.265, ICR, WDR(120dB), LEDs 30-50mt, IP67/IK10, PoE, Defog, VCA Basic

- 5 Megapixel resolution
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- Power-over-Ethernet support
- Vandal Resistant Dome (IK10)
- Built-in IR LED Illuminator
- IP67 Ingress protection

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEI-V7320TI

Technical Specifications

Image Sensor	1/2.5" Progressive Scan CMOS 5MP Aptina AR0521
Pixels - Total	2592 (H) x 1944 (V)
Video Resolution	5MP (2592 x 1944); 3.1MP (2048 x 1536); 1080P (1920 x 1080); 720P (1280 x 720); SVGA (800 x 600); D1 (720 x 480); VGA (640 x 480); CIF (352 x 240), 4MP (2560x1440)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	3.3~12 mm Motorized Autofocus
Video Outputs	1x CVBS (1Vpp), BNC
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	30/50 m (according to scene reflexion)
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
WDR	WDR Pro 120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, H.265, MJPEG, Triple Streaming
ONVIF compliant	Profile S
Max. Users	10
SD memory	supports up to 128 GB capacity of micro TF Card
Alarm	Input: 1 / Output: 1
Audio Inputs	1 in Mic
Audio Outputs	1 OUT MIC
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, SNMP, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser

Technical Specifications

Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Power Consumption (W)	9.5
Weight	0.89 kg - 1.96 lbs
Dimensions	Ø 141 mm - 5.55 In