



### Minidome Flat IP, 2MP, 2.8mm, ICR, WDR(120dB), LEDs 10mt, IP66, PoE, VCA Basic, Microphone

- 2 Megapixel IP Camera with Full HD 1080P real time video
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- Power-over-Ethernet support
- IP66 Ingress protection

### Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## SEI-F4123TI-28

### Technical Specifications

Image Sensor	1/3" CMOS Progressive Scan OV4689
Pixels - Total	2560 (H) x 1440 (V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity Colour	0.05 Lux @ F1.2
Sensitivity B/W	0 Lux LED IR on, 0.01 lux @ F1.2
Lens Focal Length	3.6 mm
Iris F-Number	F= 1.6
Horizontal Viewing Angle	95.4°
S/N Ratio	>50 dB
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	10 m
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
WDR	120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, H.265, MJPEG, Triple Streaming
Video Resolution	1920x1080 (1080p), 1280x720 (720p), 720x576 (D1)
ONVIF compliant	Profile S
Max. Users	10
Audio Inputs	1 in Mic
Audio Compression	G.711A
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IP66, IK10
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-20°C ~ +50°C
Humidity	10 ~ 90%RH
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Power Consumption (W)	3.5
Weight	0.345 kg - 0.76 lbs
Dimensions	Ø 110 mm - 4.33 In