

# DB992IVAS

**Base sirena per rilevatori serie 950/990 completa di avvisatore ottico VID e isolatore di linea**

## General

---

The DB992IVAS sounder beacon base is a multifunctional devices comprising of a mounting base for Series 990 fire detectors, a sounder, a beacon and a short circuit isolator. It is used to provide audible and visual warning of a fire alarm in an enclosed area. The DB992IVAS may be used either with a detector fitted or with a cap for operation as a stand-alone alarm device.

## Tone and Volume Selecteion

---

The DB992IVAS offers a choice of 15 evacuation and 15 alert tones. Two tones may be selected during installation, one for evacuation and one for alert. Volume levels may be selected during commissioning to one of 7 pre-set levels, with output ranging from 60 dB(A) to 90 dB(A). The low volume range is useful in areas such as hospitals where the alert is initially intended to warn staff only.

During commissioning the sounder volume can be adjusted on location without disassembly or removal. With the CIE in "setup" mode, the commissioning engineer is able to adjust the volume using a magnetic wand. Once all sounders have been adjusted, "setup" mode on the CIE is cancelled and all sounder volume levels are stored in the sounder.

## Group Addressing and Control

---

When multiple sounder/beacons in an area always need to be activated simultaneously, the DB992IVAS group addressing can be stored in each device, allowing the CIE to activate the group with a single command.

The installation also has free selection from the CIE on use of sounder only, beacon only or combined sounder/beacon operation. Functionality can be changed during time schedules, or time delays as is required per individual location.



## Dettagli

---

- Supports 15 evacuation and 15 alert tones
- 7 Volume levels
- Individual or software defined, group addressing
- Independant sounder and beacon control
- Set-up and testing at point on installation
- Built in isolator with status information

# DB992IVAS

Base sirena per rilevatori serie 950/990 completa di avvisatore ottico VID e isolatore di linea

## Specifiche tecniche

### Elettrico

Operating voltage	17 to 28 VDC
-------------------	--------------

### Fisico

Physical dimensions	115 x 38 mm (Ø x H)
---------------------	---------------------

Peso netto	160 g
------------	-------

### Ambientale

Temperatura operativa	-20 to +60°C
-----------------------	--------------

Relative humidity	0 to 95% noncondensing
-------------------	------------------------

Environment	Interno
-------------	---------

IP rating	IP21D
-----------	-------

### Operating voltages

Protocol pulses	5 - 9 V
-----------------	---------

### Current consumption at 24 V

Switch-on surge, <1s	1.2 mA
----------------------	--------

Quiescent	350 µA
-----------	--------

Activated (max. volume)	8 mA
-------------------------	------

### Sound output

Maximum at 90°	90db(A) ± 3dB(A)
----------------	------------------

Sound pressure level	Tone dependent
----------------------	----------------

### Environmental

Humidity (no condensation)	0 - 95%
----------------------------	---------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita [it.firesecurityproducts.com](http://it.firesecurityproducts.com) online o contatta il tuo riferimento commerciale.

Last updated on 7 September 2023 - 14:53