

## OH-NETREC-100

#### Osborne Hoffman network receiver. licensed software, 100 panels

#### The OH-NetRec

The Network Receiver software serves the proprietary monitoring provider as well as the traditional or contract central stations. The receiver will monitor all alarm activity and control communication using Carrier Fire & security IP transmitters in the various panels and devices.

#### Alarm transmission

The communication between OH NetRec receiver and alarm transmitters is secured using 3DES encryption. The connection between transmitters and the receivers is continuously monitored using a polling mechanism (heartbeat). Depending on the interface to the automation software (IP versus RS232) and the polling interval the max number of supported accounts is 1,000.

For EN50131 grade 3 environments the receiver also supports enhanced substitution detection.

#### **OH-NetRec capabilities**

most versatile controls in the world.

The Network receiver software can effectively monitor up to 1,000 controls with very little bandwidth required.


Multiple receivers may be used to support the dual, split, or backup TCP/IP reporting of the different TCP/IP Reporting modules.

Whether a university, large retailer, or traditional central station, the OH Network Receiver is a powerful receiver handling the finest and

Either Contact ID, SIA format or X-SIA reporting (ATS only) is supported and all of the major automation providers support the OH protocol and the Sur-Gard protocol (selectable) to send alarm information to automation. Additional signals are generated for Line Faults (alarm transmitter not responding) and substitution detected. The receiver offers a complete and secure solution for network and Internet monitoring.

#### **Additional features**

The receiver supports callback for up/download purposes when combined with the Multi-User Downloader (ATS8550). In environments where the IP address of the alarm transmitter changes regularly, Up/Download can only be achieved when the IP address is known. As the alarm transmitter is continuously connected to the receiver for supervision purposes the receiver is able to instruct the transmitter to start an up/download session.



#### Details

- Java based, supported Windows 10, Windows 7, Windows 8.x, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2 and Windows XP
- Connects over networks using Ethernet with 10- BaseT/100-BaseT
- Heartbeats used to provide supervision of availability as well as substitution detection
- Monitors and supports 1,000 control panels
- RS232 serial port or IP connection to automation computer
- Supports SIA and Contact ID formats (all transmitters)
- Support X-SIA (ATS1806/1809 or Advisor Advanced-IP and through TDA74xx module)
- Supports both OH2000E protocol & Sur-Gard protocol on the RS232 output
- Supports the OH2000E protocol to MAS Automation over TCP/IP
- Required hardware depends on number of supported accounts

# OH-NETREC-100 Osborne Hoffman network receiver. licensed software, 100 panels

### **Technical specifications**

General	
Product line	2X, Advisor Advanced, ATS Master, CS, ZP2
Segmentation	Commercial
Software type	Monitoring software
Supported technology	Intrusion
Software details	
Software architecture	Standalone
License type	Standard (Basic), Upgrade
System requireme	nts
Supported operating system	Windows 10, Windows 7, Windows 8.x, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows XP
Minimum system requirements	Intel Dual Core I5 with 4 GB RAM
OH-NETREC-SOFT	WARE
Automation protoc	col
IP	OH2000E
RS232	Sur-gard MLR, OH2000
Connection super	vision
Polling	Yes
Substitution detection	Yes
Up/Download calls	pack
Using ATS8550	Yes
PC hardware (reco	ommended minimum)
Processor	Dual core, 2.4GHz
Memory	2GB
Operating system	Windows 7
	Windows Server 2008
	32 and 64 bit
Supported devices	3
Advisor Master	ATS1806
	ATS1809
Advisor Advanced	ATS1000A-IP
	ATS2000A-IP
	ATS7310
CSX75	CS7050(N)
	CS9104/9204
	CS7002(N)
NetworX	NX590(N)E
	NX-7002(N)(V3)



NX-9104/9204

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurity products.com online or contact your sales representative.