

BS133N Battery 12 V 65 Ah



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS133N Battery 12 V 65 Ah

Technical specifications

| General | |
|--------------------------------|--------------------------|
| Product type | Sealed lead acid battery |
| Electrical characte | ristics |
| Nominal voltage | 12 V |
| Nominal capacity | 65 Ah |
| Internal approx. resistance | 10 mOhm |
| Charge / discharge | |
| Max. charge voltage | 13.8 VDC at +20°C |
| Max. charge current | 19.5A |
| Max. discharge current | 325 A |
| Temperature | |
| Charging temperature | 0 to +40°C |
| Discharging temperatur | e-15 to +50°C |
| Physical | |
| Physical dimensions | 350 x 166 x 174 mm |
| Net weight | 23.0 kg |
| Shipping weight | 23.0 kg |
| Material | ABS |
| Terminal type | MS bolt & nuts |
| Environmental | |
| Fire retardant | No |
| Operating temperature | 0 to +40°C |
| Storage temperature | -15 to +50°C |
| Regulatory | |
| Compliancy | CE, RoHS 2, WEEE |

VdS



Certification

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.