

**Minidome IP, FullHD, 2,8mm, ICR, dWDR, LEDs 20-30mt, IP67, IK10, PoE, STARLIGHT**

- 2 Megapixel Sony IMX307 Starlight CMOS
- ONVIF protocol support
- Web Browser Viewer
- Power-over-Ethernet support
- Built-in IR LED Illuminator
- IP 67 Certification
- Vandal Resistant Dome (IK10)

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/2,8" CMOS Progressive Scan Sony Starvis Starlight IMX307
Pixels - Total	1920(H) x 1080(V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.005 lux @ F1.6
Lens Focal Length	2.8 mm
Iris F-Number	F=1.85
Horizontal Viewing Angle	99.7°
S/N Ratio	>50 dB
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	20/30m (according to scene reflexion)
WDR	D-WDR (Digital wide dynamic range)
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, MJPEG, H.265
Video Resolution	1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps)
ONVIF compliant	Profile S
Max. Users	3
Motion Detection	Yes
Web Browser	All major browsers are supported
Network Protocol	UPnP, HTTPS, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Micro SDHC memory:	microsd card slot up to 128GB
Power Consumption (W)	6
Weight	0.63 kg - 1.39 lbs
Dimensions	Ø 119 mm - 4.69 In