


MTPADP-EH-SA

STANDALONF KEYPAD + REID READER

MTPADP-EH-SA is a backlit standalone keypad with EM & 125 kHz HID RFID integrated.

It comes with a built-in relay and a stylish black ABS housing. It has capacity for 1000 codes/cards.

Green **LED** Relay status (output 1)



- FEATURES -

- Multi protocol peripheral keypad
- EM 4002/4100 and HID (125 kHz) reading type
- User capacity: 1000 Cards/PIN codes
- Entry mode: codes/ cards/ codes or cards/ codes and cards
- Resin Potted Electronics
- RS485 interface: for connecting I/O boards like RB0408, RTT, RU2, DINRTT
- Firmware upgrade: via RS485 converter
- Security: 30 seconds lockout after 8 consecutive invalid PIN codes or cards

SPECIFICATIONS -

Electrical Characteristics:

Operating Voltage: 12 - 24 V AC/DC Current consumption: Maximum 100 mA

Read range: Up to 4 cm

1 built-in relay - 2A 30 V AC/DC Output:

2 relays - when used with RTT,

3 relays - when used with RU2 or DINRTT 9 relays - when used with RB0408 I/O board

Latch or pulse mode (01-99 s) Relay time:

Backlight control: Blue LED, controlled via menu settings

Visual Signals: Green, red and orange LED for status control

Audible Signal: 1 internal buzzer

Antitamper protection:

Environmental Characteristics:

Operating Temperatures: -20°C to +50°C

Operating Humidity: 0 to 95% (non-condensing)

Protection standard: **IP65**

DIMENSIONS





Black Edition Ref: MTPADPBK-EH-SA

Black - ABS



Ref: MTPADPS-EH-SA

Silver - ABS

FOBS & CARDS







Ref.	PBX-1E
Features	ABS Keyfob EM

PBX-2 0.75 mm ISO Card - EM

PBX-2C 2 mm NISO Card - FM

RELATED PRODUCTS



RBO408:





RU2:

Additional 2 relay board



Ref.

DINRTT: Push button + additional 2 relay board



RTT: Push button + additional 1 relay board

All product specifications are subject to change without notice.