

SER-6D0410TEF

DVR 5in1 960H/HD-TVI/AHD/HD-CVI/IP, 4 Input plus 2 IP, 100fps@720p/960H o 48fps@1080p/4MPLite o 40fps@5MPLite più 2 IP 5MP/6Mbps, HDMI/VGA/SPOT, I/O, Fanless

- 5 Hybrid Support 960H/HD-TVI/AHD/HD-CVI/IP
- Operating System - Linux Embedded
- H265 for high compression rate and stable stream control
- Pentaplex: preview, record, playback, backup and remote access
- HDMI - High Definition Multimedia Interface
- Fanless Design
- Free DDNS service
- Real-Time Recording @ 720p, 12fps@1080p/4MPLite or 10fps@5MPLite for each channel

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SER-6D0410TEF



Technical Specifications

Operating System	Embedded Linux
Basic Internal Storage	0 GB
Max. Storage Capacity	1 Hard disk (3.5 inch SATA), up to 8TB
External Backup	USB Memory, Network
Video Inputs	4 CH 960H/HD-TVI/AHD Max 5 Mpx /HD-CVI Max 4Mpx(BNC) + 2 CH IP, up to 6ch IP
Video Outputs	1x VGA, 1x BNC (spot out), 1x HDMI
Display resolution	max. 1920 x 1080
Video Compression	H.265, Single/ Dual Stream
Recording Mode	Continuous, Event Alarm, Motion, Schedule
Recording Speed	5MPLite 10fps, 4MPLite\1080p 12fps, 1080Lite\720p 25fps for channel
HDMI/VGA output	5MPLite (Only TVI-AHD), 4MPLite, 1080P, 720p
Audio Inputs	4 CH, RCA
Audio Outputs	1 CH, RCA
Alarm Inputs	4
Alarm Outputs	1
Motion Detection	On/ Off/ Area Setting
Alarm Trigger	Motion detection, Alarm Input, Video Loss, System Exceptions
Alarm Notification	Email / FTP, Video Record, Snapshot Record, Preset on PTZ, Relay, Pop-up video
Interfaces	2x USB, 1x RS485
Serial Protocol	Pelco D, Pelco P, ...
Network Interface	1x 10/100 Base T/TX (RJ-45)
Network Protocol	DHCP, TCP/IP, HTTP, SMTP, NTP, DNS, PPPoE, DDNS, ONVIF, AutoNAT, AutoDDNS, QRCode
Bandwidth	incoming 36 Mbps, outgoing 40Mbps
Monitoring	Web viewer, CMS (Microsoft Windows & Apple iOS), Smartphone viewer (iPhone, Android)
Max. Users	10
Playback	Synchronised playback of max. 4 cameras
Search Mode	Date/Time, Event Alarm, Motion, Video Loss
Supply Voltage	12 Vdc (230 Vac power adaptor included)
Fan	Fanless
Operating Temperature	-10°C ~ +50°C

SER-6D0410TEF**Technical Specifications**

Humidity	10 ~ 90%RH
Dimensions (W x H x D)	300 x 52 x 248 mm - 11.81 x 2.05 x 9.76 In
Power Consumption (W)	10
Weight	3.1 kg - 6.83 lbs