

MM740

Contatto magnetico installazione a pavimento, con cavo corazzato, IP40

Product overview

We have the right product for every application - residential, industrial or commercial.

We have a wide range of contacts: surface-mounted, flush-mounted, floor-mounted, door-mounted.

The MM740 is well suited for roller shutter protection.



Dettagli

- Ideal for roller shutter and curtain door applications
- Armoured cable
- Tamper loop

MM740

Contatto magnetico installazione a pavimento, con cavo corazzato, IP40

Specifiche tecniche

Generale

Application type	Overhead
Contact type	NC
Connectivity	4 wires, 60 cm (armoured cable)

Cablato / senza fili

Wired-wireless	Cablato
Operating gap	max.98 mm

Elettrico

Voltage	max. 200 VDC
---------	--------------

Fisico

Dimensions magnet	78 x 43 x 47 mm
Dimensions contact / sensor	175 x 50 x 12 mm
Colour	Grigio

Ambientale

Operating temperature	-10 to +55°C
IP rating	IP40



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:53