


SEI-T8323TI



Bullet IP, 4K(8MP), 2.8-12mm MOTOR., ICR, WDR 120dB, LEDs 30-50mt, IP67/IK10, POE, H.265, VCA Basic

- 4K Resolution for super detailed images
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- ONVIF protocol support
- Power-over-Ethernet support

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/2.8" Progressive Scan CMOS
Pixels - Total	3840 (H)x 2160 (V), 25fps
Video Resolution	1280x720 (720p), 1920x1080 (1080p), 720x576 (D1), 3840 x 2160 (25fps)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity B/W	0 Lux LED IR on, 0.005 lux@F1.4
Lens Focal Length	2.8 ~ 12 mm Motorized
Horizontal Viewing Angle	104.7° (Wide) ~ 32.5° (Tele)
Video Outputs	No (n/a)
Shutter Speed	1/25 ~ 1/100,000s
Max. IR Distance	30/50 m (according to scene reflexion)
WDR	WDR Pro 120dB
Intelligent Video Analytics	Tampering, Motion /Moved-Fixed Objects /Fence /Enter-Exit Area
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR), 2D DNR (Off/On)
De-Fog	Off/On
Video Compression	H.264, H.265, Triple Streaming
ONVIF compliant	Profile S
Max. Users	10
SD memory	Micro SD/SDHC, up to 256 GB
Alarm	N/A
Audio Inputs	1 in Mic
Audio Outputs	None
Audio Compression	G.711 a/u
Web Browser	All major browsers are supported
Network Protocol	HTTPS, TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Interfaces	RS-485
Supply Voltage	12 Vdc / PoE (IEEE 802.3af)
Protection Rating	IK10, IP67
Firmware Upgrade	Firmware upgrade by Web Browser

Technical Specifications

Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Dimensions (W x H x D)	217.8 x 80.5 x 80.5 mm - 8.57 x 3.17 x 3.17 In
Power Consumption (W)	10
Weight	0.44 kg - 0.97 lbs