

**SER-6D0820TEF-LT**

**DVR 5in1 960H/HD-TVI/AHD/HD-CVI/IP, 8 In plus 1 IP, 100fps@1080pLite o 200fps/720p plus 1 IP FullHD/6Mbps, HDMI/VGA, Fanless**

- 5 Hybrid Support 960H/HD-TVI/AHD/HD-CVI/IP
- Operating System - Linux Embedded
- H.264 compression modes
- Real-Time Recording @ 720p, 12fps@1080p for each channel
- Pentaplex: preview, record, playback, backup and remote access
- HDMI - High Definition Multimedia Interface
- Fanless Design
- Free DDNS service

**Summary**

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

## SER-6D0820TEF-LT



### Technical Specifications

<b>Operating System</b>	Embedded Linux
<b>Basic Internal Storage</b>	0 GB
<b>Max. Storage Capacity</b>	1 Hard disk (3.5 inch SATA)
<b>External Backup</b>	USB Memory, Network
<b>Video Inputs</b>	8 CH 960H/HD-TVI/AHD/HD-TVI (BNC) + 1 CH IP
<b>Video Outputs</b>	1x VGA, 1x HDMI
<b>Display resolution</b>	max. 1920 x 1080
<b>Video Compression</b>	Single/ Dual Stream, H.264 High Profile
<b>Display Speed</b>	200 fps
<b>Recording Mode</b>	Continuous, Event Alarm, Motion, Schedule
<b>Recording Speed</b>	100fps @ 1080pLite, 200fps @ 720p, 200fps @ 960H + 1 x IP 25fps @ 1080p max 6Mbps
<b>HDMI/VGA output</b>	1080p Lite (960x1080 pxls), HD (1280x720 pxls), 960H (960x576 pxls)
<b>Audio Inputs</b>	1 CH, RCA
<b>Audio Outputs</b>	1 CH, RCA
<b>Alarm Inputs</b>	None
<b>Alarm Outputs</b>	None
<b>Motion Detection</b>	On/ Off/ Area Setting
<b>Alarm Trigger</b>	Motion detection, Alarm Input, Video Loss, System Exceptions
<b>Alarm Notification</b>	Email / FTP, Video Record, Snapshot Record, Preset on PTZ, Relay, Pop-up video
<b>Interfaces</b>	2x USB, 1x RS485
<b>Serial Protocol</b>	Pelco D, Pelco P, ...
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Network Protocol</b>	DHCP, TCP/IP, HTTP, SMTP, NTP, DNS, PPPoE, DDNS, ONVIF, AutoNAT, AutoDDNS, QRCode
<b>Monitoring</b>	Web viewer, CMS (Microsoft Windows & Apple iOS), Smartphone viewer (iPhone, Android)
<b>Max. Users</b>	10
<b>Playback</b>	Synchronised playback of max. 4 cameras
<b>Search Mode</b>	Date/Time, Event Alarm, Motion, Video Loss
<b>Supply Voltage</b>	12 Vdc (230 Vac power adaptor included)
<b>Fan</b>	Fanless
<b>Operating Temperature</b>	-10°C ~ +50°C

**SER-6D0820TEF-LT****Technical Specifications**

Humidity	10 ~ 90%RH
Dimensions ( W x H x D)	255 x 42 x 223 mm - 10.04 x 1.65 x 8.78 In
Power Consumption (W)	5
Weight	3.1 kg - 6.83 lbs