






KAL1248VS

Part number: KAL1248VS

Switching power supply with 4 separated outputs from 12Vdc 1A



APPLICATION FIELDS

-  RESIDENTIAL
-  COMMERCIAL
-  MEDICAL
-  PUBLIC SERVICE
-  PUBLIC ENTERTAINMENT

Installation	DIN rail
Format	home
Technology	Switching
Phase	Single
Input voltage (Vac)	100 - 240 Vac
Input current lout (A)	0,9 (115Vac) / 0,5 (230Vac)
Inrush current (A)	50
Input frequency (Hz)	50 - 60
Power Dissipation at 230Vac (W)	11
Efficiency (%)	>80

Power (W)	
Output voltage	
Adjustable Output (Vdc)	10 - 14 (outputs are not individually adjustables)
Output current (A)	1
Working temperature (°C)	-15 +60
Cooling	Natural
Derating	-
IP rating	IP20
Available contact	-
Communication	-
Signalling	DC OK
Protections	Overload, Short circuit, Thermal
Connection	Screw
Material	Plastic fire-retardant UL-94V-0
Standards	EN 61000-3-3, EN 61000-6-1, EN 61000-6-3, EN 62368-1
Classification Pelv / Selv	pelv / selv
Warranty	2 Year
Package quantity (pieces)	5
Height (mm)	90
Width (mm)	124
Depth (mm)	66
Weight (Kg)	0,35