SEI-E4126TI-H







Eyeball IP, FullHD, 2,8mm, ICR, dWDR, LEDs 20-30mt, IP67, IK10, PoE, STARLIGHT

- 2 Megapixl Sony IMX307 Starlight CMOS
- · ONVIF protocol support
- · Web Browser Viewer
- Power-over-Ethernet support
- Built-in IR LED Illuminator
- IP67, IK10

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, form retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.





SEI-E4126TI-H



| Technical Specifications | |
|--------------------------|--|
| Image Sensor | 1/2,8" CMOS Progressive Scan Sony Starvis Starlight IMX307 |
| Pixels - Total | 1920(H) x 1080(V) |
| Scanning System | Progressive |
| Col/B | On/Off/Auto |
| Sensitivity B/W | 0 Lux LED IR on, 0.005 lux @ F1.6 |
| Lens Focal Length | 2.8 mm |
| Iris F-Number | F=1.85 |
| Horizontal Viewing Angle | 99.7° |
| S/N Ratio | >50 dB |
| Shutter Speed | 1/25 ~ 1/100,000s |
| Max. IR Distance | 20/30m (according to scene reflexion) |
| WDR | D-WDR (Digital wide dynamic range) |
| White Balance | Auto / Manual |
| AGC | Auto, Manual |
| Digital Noise Reduction | Auto (3D-DNR) |
| Video Compression | H.264, MJPEG, H.265 |
| Video Resolution | 1920x1080 (25 fps), 1280x720 (25 fps), 704x576 (25 fps), 352x288 (25 fps) |
| ONVIF compliant | Profile S |
| Max. Users | 3 |
| Motion Detection | Yes |
| Micro SDHC memory: | microsd card slot up to 128GB |
| Web Browser | All major browsers are supported |
| Network Protocol | SMTP, HTTPS, IPv4/IPv6, QoS, IEEE 802.1 X, TCP/IP, UDP, DHCP, NTP, RTSP, PPP0E, DDNS, SMTP,FTP |
| Network Interface | 1x 10/100 Base T/TX (RJ-45) |
| Protection Rating | IK10, IP67 |
| Firmware Upgrade | Firmware upgrade by Web Browser |
| Operating Temperature | -30° C ~ +60° C |
| Humidity | less than 95%, non condensing |
| Supply Voltage | 12 Vdc, PoE (IEEE 802.3af) |
| Power Consumption (W) | 5 |
| Weight | 0.45 kg - 0.99 lbs |
| Dimensions | Ø 94.6 mm - 3.72 ln |
| | |

