

DMN700GE

Manual Callpoint, Green, Emergency Door Release, Free Contact, Outdoor, Surface Mount With Glass

General

The DMN700GE is a weather proof MCP, designed for outdoor application with an IP67 ingress protection rating. It comes with snap on connections, which ensure ease of installation and maintenance. Assembly of the unit is also made easy with a simple snap on fit, and 4 screws to secure the unit.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options and Approvals

Through new standards and legislation, both glass and re-settable operating elements may be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



Dettagli

- Specifically for door security and evacuation
- Easy to install
- With break glass or resettable element
- Easy to replace glass
- High quality micro switch
- IP67 rated

DMN700GE

Manual Callpoint, Green, Emergency Door Release, Free Contact, Outdoor, Surface Mount With Glass

Specifiche tecniche

Generale

Indicazione stato	Alarm flag
Compatibility	Conventional alarm systems
Connettività	2 core cable

Elettrico

Specifiche cavo	0.5 - 2.5 mm²
Numero di nucleo cavi	2

Rivelazione

Principio di rilevamento	Manual activation
Monitoraggio	Activated, Released
Altezza di installazione	Determined by local regulation

Uscita

Quantità in uscita	1
Tipo di uscita e intervallo	2 A @ 30 VDC (resistive load)

Fisico

Dimensioni fisiche	98 x 94 x 70 mm (W x H x D)
Peso netto	270 g
Colore	Verde (RAL 6016)
Tipo di montaggio	Back box, Montaggio a superficie
Materiale (scatola)	PC / ABS
Marcatura funzionale	Running man

Ambientale

Vandal proof	No
Temperatura operativa	-30 to +70°C
Umidità relativa	0 to 95% noncondensing
Ambiente	Interno, Da esterno
IP rating	IP67

Regolatorio

Compliance	CE, REACH, RoHS 2, WEEE
Certificazioni	CE

Prodotti compatibili

Categoria	Riferimento	Descrizione
Dispositivo di rivelazione	DM711	Vetrino per avvisatori manuali. Confezione da 10 pezzi
Dispositivo di rivelazione	DM715	Vetrino per avvisatori manuali (senza logo). Confezione da 10 pezzi
Dispositivo di rivelazione	DMN782	Mascherina di copertura in plastica
Dispositivo di rivelazione	DMN784	Chiave di test per avvisatori manuali (10 pezzi)
Dispositivo di rivelazione	DMN789	Replacement Pluggable Connectors For Manual Call Points (10 Pack)



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 3 July 2023 - 9:36