

10954N

Apollo Mains Switching IO Unit (SA4700-103)

General

IO954N is the new mains switching input/output unit which contains one or more normally open contacts connected to a single pair of cables. It also provides a voltage free change over relay output capable of switching mains.

Mechanical Construction

The IO954N is available in the new faceplate style enclosure. It is designed to be surface mounted to the wall and consists of 3 parts:

- a back box with knock-outs for cable entry
- a PCB assembly
- a protective front cover

Ease of Installation

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



Dettagli

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Contains one or more NO contacts connected on a single pair of cables
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

10954N

Apollo Mains Switching IO Unit (SA4700-103)

Specifiche tecniche

Elettrico	
Operating voltage	17 to 35 VDC
Fisico	
Dimensioni fisiche	150 x 90 x 60 mm
Peso netto	301 g
Ambientale	
Temperatura operativa	-40 to +70°C
Umidità relativa	0 to 95% noncondensing
Environment	Interno
Regolatorio	
Certificazioni	CPR, EN54-17, EN54-18
Electrical	
Protocol voltage	5-13V peak to peak
Current consumption	
Power-up surge	1.1 mA
Quiescent	0.7 mA
LEDs disabled (max.)	0.7 mA
Alarm (LEDs On) (max.)	5.2 mA



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.