

SEI-F6124TI-28



Minidome Flat IP, 4MP, 2.8mm, ICR, WDR(120dB), LEDs 10-20mt, IP66, PoE, Advanced VCA, Microfono, NDAA.

- 4 Megapixel IP Camera with real time video streaming
- H265 for high compression rate and stable stream control
- Triple-streaming support
- Advanced Analytics with car\human\bike classification
- Built in analytics function, motion detection, trip wire, intrusion detection, tamper detection
- Power-over-Ethernet support
- IP66 Ingress protection

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

Technical Specifications

Image Sensor	1/2.8" Progressive Scan CMOS
Pixels - Total	2592 (H) x 1520 (V)
Scanning System	Progressive
Col/B	On/Off/Auto
Sensitivity Colour	0.0028 Lux @ F1.2
Sensitivity B/W	0 Lux LED IR on
Lens Focal Length	2.8 mm
Iris Operation	Fixed Iris
Iris F-Number	F= 1.6
Horizontal Viewing Angle	100.4°
S/N Ratio	>50 dB
Shutter Speed	1/30 ~ 1/100,000s
Max. IR Distance	10 m
Intelligent Video Analytics	Tampering, Scene change detection, masking of the camera lens, Unattended Baggage, Area Entrance, Virtual fence
WDR	120dB
White Balance	Auto / Manual
AGC	Auto, Manual
Digital Noise Reduction	Auto (3D-DNR)
Video Compression	H.264, H.265, MJPEG, Triple Streaming
Video Resolution	1920x1080 (1080p), 1280x720 (720p), 720x576 (D1), 4MP 2592 (H) x 1520 (V)
ONVIF compliant	Profile S
SD memory	up to 256 GB
Max. Users	10
Audio Inputs	1 in Mic, Built in Microphone
Audio Compression	G.711A
Advanced Video Analytics	Advanced video Analytics A: Area intrusion\line crossing with Object Classification (Human, Vehicle, Bike). Remove object, Face detection&tracking, crowd detection, people counting, car counting, heat mapping, human & face tracking.
Corridor Mode	Supported
Motion Detection	Yes
Web Browser	All major browsers are supported

Technical Specifications

Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Network Interface	1x 10/100 Base T/TX (RJ-45)
Protection Rating	IP66, IK10
MTBF at 25° C	120.000 hours
Firmware Upgrade	Firmware upgrade by Web Browser
Operating Temperature	-30° C ~ +60° C
Humidity	less than 95%, non condensing
Supply Voltage	12 Vdc, PoE (IEEE 802.3af)
Power Consumption (W)	6
Weight	0.349 kg - 0.77 lbs
Dimensions	Ø 110 mm - 4.33 In