

SEN-G4280HP1


NVR 4 In, H.265, max 5MP, 28Mbps, 4 POE, HDMI 2K, VGA, Fanless.

- Operating System - Linux Embedded
- Support up to 5MP Resolution Recording
- H.264/H.265 compression modes
- Built in PoE Switch for direct IP camera connection
- Pentaplex: preview, record, playback, backup and remote access
- Smart Phone support Android, iPhone and iPad
- ONVIF protocol support
- Free DDNS service

Summary

Skilleye is a new brand of Professional CCTV products, a perfect combination of high quality and cost effective prices. Skilleye was created to answer to installer needs, from retail to Pharmacy, offices or hotels, you can be sure to find the right product. High quality components, regular and severe tests, a large range, these are the secrets of Skilleye.

SEN-G4280HP1

Technical Specifications

Operating System	Embedded Linux
Multiplex Function	Pentaplex
Basic Internal Storage	0 GB
Max. Storage Capacity	1 Hard disk (3.5 inch SATA), up to 6TB per disk
Video Inputs	4 IP cameras
Recording Bandwidth	max 28Mbps
HDMI/VGA output	Up to 5 Megapixel
Video Compression	H.264, H.265
Video Streaming	2 independent Video-Streams
Video Outputs	1x VGA, 1x HDMI
Display Speed	100 fps
Recording Mode	Manual, Schedule, Motion, Alarm
Audio Outputs	1x HDMI
Audio Inputs	camera microphone
Alarm Inputs	None, Support IPC alarm input
Alarm Outputs	None
Motion Detection	On/ Off/ Area Setting
Alarm Trigger	Alarm Input, Manual Trigger, Motion detection, System Exceptions, Video Loss
Alarm Notification	Email / FTP, Pop-up video, Preset on PTZ, Snapshot Record, Video Record
Interfaces	2 x USB 2.0
Network Interface	10/100 Base-T
Network Protocol	AutoDDNS, AutoNAT, DDNS, DHCP, DNS, NTP, PPPoE, QRCode, SMTP, TCP/IP, UPnP
Monitoring	Web viewer, CMS (Microsoft Windows & Apple macOS), Smartphone viewer (iOS, Android)
Max. Users	10
Playback	Synchronised playback of max. 4 cameras
Search Mode	Time, Motion, Alarm, Timeline
Smart Search Function	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
External Backup	USB HDD, USB Memory, Network
Supply Voltage	48 VDC, Power adaptor included
ONVIF compliant	Yes

SEN-G4280HP1**Technical Specifications**

Operating Temperature	-10°C ~ +50°C
Fan	Fanless
Operating Humidity	10% ~ 90%, non-condensing
Dimensions (W x H x D)	255 x 42 x 233 mm - 10.04 x 1.65 x 9.17 In
Power Consumption (W)	6
Weight	2.3 kg - 5.07 lbs